

General Description:

1k surfacer is modified alkyd pigmented undercoat based on alkyd and selected pigments. For indoor, which reduces the number of coats required, fast curing and flexible.

Major Uses:

Hard polyurethane foam in general,

Characteristics and Physical Properties:

Appearance	Liquid
Colour	As required
Weight solids	80%
0 Viscosity @ 25 C	10 000-12 000 cP
Dilution	20-40 %
Dilution solvent	Zure solve 5

Drying Time:

Dust free	10-15 min.
-----------	------------

To touch	20-30 min.
Hard Dry	4 hrs.

Method of Application:

By spraying (3- 4 atm)

- To the surface well prepared, apply 1 – 2 Coats of 1k Surfacer vertically and horizontally...□

Storage:

0 Keep material in a cool place below 25 C. Keep the container tightly closed. Shelf life of 2 Years.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner.

Packing:

Available in 20 Kg.

Physiological Hazards:

1k Surfacer do not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. 1k Surfacer is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.

Zurechem Coatings

New Borg EL-Arab city, 2nd industrial Zone, Alex., Egypt
 Tel/fax. : (+203) 4625400
 Tel/fax.: (+203)4625399
 Customer service: +20122207225
 contact@zurechem.com
 www.zurechem.com

