

# ROAD MARKING PAINT (solvent base)

## DESCRIPTION: -

solvent based road and marking paint.

## CHARACTERISTICS:-

- Interior and exterior use.
- Developed to give good adhesion to concrete and asphalt.
- Excellent abrasion resistance.
- Excellent hiding power.
- Good reflection properties.
- Very quick drying.
- Easy to apply.

## COLOUR

White, yellow and black

GLOSS: Matt

## BASIC DATA AT 25 °C

Density	1.62±0.02 g/cm <sup>3</sup>
Solids content	70%
Recommended dry film thickness	40 µm
Touch dry after	30 minutes
Shelf life (cool, dry place)	24 months

Available pack size: pail 20liter

## RECOMMENDED SUBSTRATE CONDITIONS

concrete and asphalt surfaces must be sufficiently dry and free from dirt, grease, laitance and any other contamination

# ROAD MARKING PAINT (solvent base)

## SYSTEM SPECIFICATION

quick drying paint to be applied in two coats for marking lines and patterns on concrete and asphalt surfaces.

## INSTRUCTIONS FOR USE

### AIR SPRAY

<b>Recommended thinner</b>	solvent
<b>Volume of thinner</b>	5 - 10%
<b>Nozzle orifice</b>	1.5 – 1.8 mm
<b>Nozzle pressure</b>	2 – 3 bar

### BRUSH AND ROLLER

<b>Recommended thinner</b>	solvent
<b>Volume of thinner</b>	5 - 10%

<b>CLEANING SOLVENT</b>	solvent
-------------------------	---------

### **Zurechem Coatings**

New Borg EL-Arab city, 2nd industrial Zone, Alex., Egypt  
Tel/fax. :(+203) 4625400 Tel/fax. :(+203)4625399  
Customer service: +20122207225  
contact@zurechem.com www.zurechem.com