

ROAD MARKING PAINT (Water base)

DESCRIPTION: -

Water based road and marking paint.

CHARACTERISTICS:-

- Interior and exterior use.
- Developed to give good adhesion to concrete and asphalt.
- Excellent abrasion resistance.
- Excellent hiding power.
- Good reflection properties.
- Very quick drying.
- Easy to apply.

COLOUR

White, yellow and black

GLOSS: Matt

BASIC DATA AT 25 °C

Density	1.62±0.02 g/cm ³
Solids content	70%
Recommended dry film thickness	40 μm
Touch dry after	30 minutes
Shelf life (cool, dry place)	24 months

Available pack size: pail 20liter

RECOMMENDED SUBSTRATE CONDITIONS

concrete and asphalt surfaces must be sufficiently dry and free from dirt, grease, laitance and any other contamination

ROAD MARKING PAINT (Water base)

SYSTEM SPECIFICATION

quick drying paint to be applied in two coats for marking lines and patterns on concrete and asphalt surfaces.

INSTRUCTIONS FOR USE

AIR SPRAY

Recommended thinner	water
Volume of thinner	5 - 10%
Nozzle orifice	1.5 – 1.8 mm
Nozzle pressure	2 – 3 bar

BRUSH AND ROLLER

Recommended thinner	water
Volume of thinner	5 - 10%

CLEANING SOLVENT	water
-------------------------	-------

Zurechem Coatings

New Borg EL-Arab city, 2nd industrial Zone, Alex., Egypt
Tel/fax. :(+203) 4625400 Tel/fax. :(+203)4625399
Customer service: +20122207225
contact@zurechem.com www.zurechem.com