

General Description:

Acrylic Surfacers 4:1 is an acrylic pigmented undercoat based on special acrylic resin and selected pigments. A two-component material with outstanding characteristics, giving a good adhesion on hard polyurethane foam. It has good weather resistance, fast curing and flexible. UV resistance

Major Uses:

Polyurethane hard foam in general and also wood furniture

Characteristics and Physical Properties:

Appearance	Liquid
Colour	As the sample
Weight solids	80%
0 Viscosity @ 25 C	8000-12000 cP
Dilution	10-20%
Mix ratio by weight	4:1

Drying Time:

Dust free	10-15 min.
To touch	20-30 min.
Hard Dry	4 hrs.

Method of Application:

By spraying (3- 4 atm)

- To the surface well prepared, apply 1 – 2 Coats of acrylic Surfacers 4:1 with Hardener vertically and horizontally...□

Storage:

0 Keep material in a cool place below 25 C. Keep the container tightly closed. Shelf life of 1 Year.

Cleaning of Tools:

All tools should be cleaned with Zure Wash Thinner.

Packing:

Available in 20 Kg.

Physiological Hazards:

acrylic Surfacers 4:1 and acrylic Surfacers Hardener do not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. acrylic Surfacers 4:1 is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.

Zurechem Coatings

New Borg EL-Arab city, 2nd industrial Zone, Alex., Egypt
Tel/fax. : (+203) 4625400
Tel/fax.: (+203) 4625399
Customer service: +20122207225
contact@zurechem.com
www.zurechem.com